



EOLAD™
LASER WITH HOLOGRAPHIC WEAPON SIGHT

The impressive *EOLAD* combines the power and precision of a Laser Devices' laser with the speed and proven effectiveness of the L-3 EOTech 552 HWS combat optic. This single, cutting-edge device provides lightening fast target acquisition and delivers impeccable shooting accuracy in ever-changing battlefield conditions.

Designed to military standards to withstand temperature, shock and vibration, the *EOLAD* is the right combination to

handle the most extreme law enforcement and military operations with ease.

Single beam models are available with either an infrared or visible pointer. Dual Beam models are available with either an infrared or visible pointer and an IR pointer/illuminator. Visible pointers are available with your choice of a red Super Power Point™ or green Ultra Power Point™ laser which is five times more visible than traditional red lasers.

EOLAD-1



EOLAD-2



EOLAD-1V

- Choice of
 - Red Visible Pointer (<5mW) or
 - Green Visible Pointer (<5mW or <50mW)

***EOLAD-1I**

- IR Pointer (<5mW or <50mW)

***EOLAD-2I**

- IR Pointer (<5mW)
- IR Pointer/Illuminator (<50mW)

***EOLAD-2H**

- IR Pointer (<50mW)
- IR Pointer/Illuminator (<50mW)

****EOLAD-2S**

- IR Pointer (<50mW)
- IR Pointer/Illuminator (<200mW)

***EOLAD-2VI**

- IR Pointer/Illuminator (<5mW)
- Choice of
 - Red Visible Pointer (<5mW) or
 - Green Visible Pointer (<5mW)



*LE/Military only
**Military only



LASER FEATURES INCLUDE


- ▶ Rugged aerospace aluminum housing, MIL-SPEC Type III hardcoat anodized
- ▶ Hi- and Lo-power modes of operation
- ▶ Meets MIL-STD-810G for adverse environmental conditions
- ▶ Activation and low battery indicator light
- ▶ Fully adjustable windage and elevation
- ▶ Remote cable switch and integrated activation switch
 - Single tap enables momentary laser activation
 - Double tap instantly activates the laser in a continuous ON mode for 5 minutes or until pressed again
- ▶ Supplied with
 - EOTech 552 Holographic Weapon Sight
 - Integrated Picatinny Mount
 - Batteries
 - 10" remote cable pressure pad switch
 - Nylon pouch
- ▶ Optional pattern generators (NSN #1240-01-537-0496), optical diffuser and neutral density filter available for infrared models
- ▶ Manufactured in the U.S.A.

EOLAD ACCESSORIES



Right Angle Remote Cable

OPTIONAL



Pattern Generators (set of 5)



Optical Diffuser



Neutral Density Filter



Remote Cable

EOLAD SPECIFICATIONS SEE PAGE 35 FOR ADDITIONAL SPECIFICATIONS & WARRANTY

LIMITED WARRANTY	2 years
MATERIAL	Anodized aircraft aluminum 6061T-6
WEIGHT (WITH BATTERY)	16.8 ounces / 476.3 grams
SIZE	L 5.5 in. x W 2.4 in. x H 2.4 in. / L 14 cm x W 6 cm x H 6 cm
ENVIRONMENT	Waterproof to 10 meters
BATTERY	Two 1.5-volt AA
BATTERY LIFE	Up to 20 hours continuous