

# DBAL-I<sup>2</sup>™

## DUAL BEAM AIMING LASER-INTELLIGENT<sup>2</sup>

The NEW DBAL-I<sup>2</sup> is the cutting-edge replacement for the AN/PEQ-2A combining an infrared laser pointer and infrared pointer/illuminator in a lightweight, rugged metal housing.

The DBAL-I<sup>2</sup>

- Provides the same functionality
  - Is smaller and lighter
  - Is significantly shorter and leaves more rail space for other accessories
  - Mirrors the AN/PEQ-2A activation switch options
- Built to perform under the

most rigorous conditions and survive the harshest environments, the DBAL-I<sup>2</sup> provides operators with a critical tool for use with night vision devices.

Available in Desert Sand or Black.

### DBAL-I<sup>2</sup>

- IR Pointer (<50mW)
- IR Pointer/Illuminator (<50mW or <\*200mW)
- Optional red or green Visible Pointer (<5mW) with IR Pointer (<5mW)

LE/Military only  
\*Military only



### FEATURES INCLUDE

- ▶ Rugged aerospace aluminum housing, MIL-SPEC Type III hardcoat anodized
- ▶ Hi- and Lo-power modes of operation
- ▶ Meets MIL-STD-810G requirements
- ▶ ESD compliant for air worthiness
- ▶ Activation / low battery indicator light (123A battery only)
- ▶ Remote cable pressure pad switch and integrated momentary activation switch
  - Single tap enables momentary activation
  - Double tap activates the laser in a continuous ON mode
- ▶ Fully adjustable windage and elevation
- ▶ Supplied with
  - Quick Release HT Mount (Patent Pending)
  - Pattern generators (NSN #1240-01-537-0496)
  - Battery
  - 7" remote cable pressure pad switch
  - Nylon pouch
- ▶ Optional optical diffuser, neutral density filter, sub-miniature red dot sight, MIL-SPEC-1913 top rail or flip-up front sight
- ▶ Manufactured in U.S.A.



**DBAL-I<sup>2</sup>**  
 simulated IR Pointer &  
 IR Illuminator



**NEW! CLASS I IR LASERS**



**NEW!**  
**DBAL-I<sup>2</sup>**  
 with Class I, Eye-Safe  
 Infrared Pointer &  
 Class IIIa Visible Pointer



**AVAILABLE WITH THE FOLLOWING OPTIONS:**

- ▶ Red visible pointer (<5mW) & Class I, Eye Safe IR pointer (≈0.7mW) or
- ▶ Green visible pointer (<5mW) & Class I, Eye Safe IR pointer (≈0.7mW) or
- ▶ Quick Release HT Mount (Patent Pending)
- ▶ 7" remote cable pressure pad switch
- ▶ One 3-volt 123A Lithium or One 1.5-volt AA battery
- ▶ Available in Desert Sand or Black

Call 800-235-2162 or visit [www.laserdevices.com](http://www.laserdevices.com) for additional information.

**DBAL-I<sup>2</sup> ACCESSORIES**



OPTIONAL



**DBAL-I<sup>2</sup> SPECIFICATIONS** SEE PAGE 35 FOR ADDITIONAL SPECIFICATIONS & WARRANTY

MATERIAL	Anodized aircraft aluminum 6061T-6
WEIGHT (WITH BATTERY)	7.2 ounces / 201.3 grams
SIZE	L 3.5 in x W 2.75 in x H 1.75 in / L 8.9 cm x W 7 cm x H 4.4 cm
ENVIRONMENT	Waterproof to 20 meters
BATTERY	One 3-volt 123A Lithium or One 1.5-volt AA (except on <200mW model)
BATTERY LIFE	Up to 5 hours continuous