

Power Breezer Titan



O2 Titan



TECHNICAL SPECIFICATIONS

	VOLTS	GOVT. GRADE PART NUMBER	VOLTS	GOVT. GRADE PART NUMBER
	220V	PB20-A-1-F	220V	MG-AB20-A-1F
Cooling Ability	Up to 15°C (27°F)		Up to 15°C (27°F)	
Area of Coverage (Optimal)	Up to 279m ² (3,000 sq. ft.)		Up to 140m ² (1,500 sq. ft.)	
Effective Distance	Up to 24 meters (80 feet)		Up to 12.2 meters (40 feet)	
Oscillation	Yes		Yes	
Integrated Water Container	Yes - 303 liters (80 gallons) Hose connection not required.		Yes - 151 liters (40 gallons) Hose connection not required.	
Operating Time	4-5 days running 8 hours a day		4-5 days running 8 hours a day	
Effective Water Vaporization	0.4L-7.6L/Hour (0.1-2 Gallons/Hour)		0.4L-3.6L/Hour (0.1-.95 Gallon/Hour)	
Electric Consumption	Avg. 5 Amps, 1,100 Watts (220V Unit)		Avg. 4 Amps, 880 Watts (220V Unit)	
Air Flow	23,786 m ³ /hr (14,000 CFM)		16,990 m ³ /hr (10,000 CFM)	
Height	116.8cm (46") stored, 177.8cm (70") mounted		106cm (41.75") stored 161cm (63.3") mounted	
Width	75cm (29.5")		67cm (26.3")	
Depth	107cm (42") stored, 130.8cm (51.5") mounted		94cm (37.0") stored 112cm (44.1") mounted	
Weight (without water)	99.8kg (220 lbs.)		80kg (176 lbs.)	
Power Source	220V (Type G Plug)		220V (Type G Plug)	
Motor	1 hp E		1 hp E	
Technology	Unique atomization technology		Unique atomization technology	
Highly durable casters	25.4cm (10") and 20cm (8") rugged locking wheels/casters		20.3cm (8") and 15.2cm (6") rugged wheels/locking casters	
Hard case for shipping and transport	Yes - Integrated into design		Yes - Integrated into design	
Certifications	OSHA Compliant, ETL Certified, NOM Certified, CE Compliant (220V unit) SASO Compliant, MIL-STD 810G		OSHA Compliant (ETL, NOM, CE, SASO, MIL-STD 810G Certifications Pending)	
Warranty	2 Years		2 Years	